



NOTES:

1. P1 STATIC FORCE AT 20°C: 1200N (+/-60N)
2. DAMPING ZONE 53mm (40mm) STANDARD OIL
3. SYMBOLISE TO SPEC 'D' (00-3816)
4. MATERIALS OF CONSTRUCTION:
ROD - BLACK NITRIDED CARBON STEEL
TUBE - BLACK EPOXY COATED CARBON STEEL
VALVE - BRASS

END FITS:

ROD - STEEL, ZINC & TRIVALENT PASSIVATE
TUBE - STEEL, ZINC & TRIVALENT PASSIVATE

Supplied by H. A. Guden Co., Inc. 800-344-6437 guden.com Guden P/N: 544334-1009

Camloc
Motion Control

CAMLOC MOTION CONTROL LTD
Manufacturers of *Camloc* Gas Springs
15 New Star Road, Leicester, LE4 9JD, England
Tel: +44 (0) 116 274 3600
Email: info@camloc.com
Website: www.camloc.com

DRAWING DATA

DRAWN: HL	PROJECT N°: SALES
DATE: 17/5/2023	
SCALE: 1:1	

TITLE:

**10-23 SWIFT & SURE
GAS SPRING ASSEMBLY**

CUSTOMER: H A GUDEN

PART N°:
SWV1B5400460B5D

REV: