

**NOTES:**

1. P1 STATIC FORCE AT 20°C: 2500N (+/-125N)
2. DAMPING ZONE 91mm (60mm) STANDARD OIL
3. SYMBOLISE TO SPEC 'D' (00-3816)
4. MATERIALS OF CONSTRUCTION:  
 ROD - BLACK NITRIDED CARBON STEEL  
 TUBE - BLACK EPOXY COATED CARBON STEEL  
 VALVE - BRASS

**END FITS:**

ROD - STEEL, ZINC & TRIVALENT PASSIVATE  
 TUBE - STEEL, ZINC & TRIVALENT PASSIVATE

Supplied by H. A. Guden Co., Inc. 800-344-6437 guden.com Guden P/N: 544878-0210

**Camloc**  
 Motion Control

**CAMLOC MOTION CONTROL LTD**  
 Manufacturers of *Camloc* Gas Springs  
 15 New Star Road, Leicester, LE4 9JD, England  
 Tel: +44 (0) 116 274 3600  
 Email: info@camloc.com  
 Website: www.camloc.com

**DRAWING DATA**

DRAWN: HL	PROJECT N°: SALES
DATE: 19/5/2023	
SCALE: 1:1	

**TITLE:**

**14-28 SWIFT & SURE  
 GAS SPRING ASSEMBLY**

CUSTOMER: H A GUDEN

PART N°:  
**SWV4B6500575B6D**

REV:

**1**



CAMLOC MOTION CONTROL LIMITED - THE DESIGN AND INFORMATION CONTAINED IN THIS DRAWING IS STRICTLY CONFIDENTIAL. IT IS THE EXCLUSIVE PROPERTY OF CAMLOC MOTION CONTROL LIMITED AND MUST NOT BE USED, COPIED OR REPRODUCED IN PART OR WHOLE WITHOUT WRITTEN PERMISSION FROM CAMLOC MOTION CONTROL LIMITED

**DRAWING IS  
 COMPUTER GENERATED.  
 DO NOT HAND MODIFY.**

**IF IN  
 DOUBT,  
 ASK.**

**DRAWING UNCONTROLLED WHEN  
 PRINTED PLEASE CHECK ORDER  
 REVISION LEVEL BEFORE MANUFACTURE**

DRAWING N°:  
**SWV4B6500575B6D\_S**