



**NOTES:**

1. P1 STATIC FORCE AT 20°C: 650N (+/-33N)
2. DAMPING ZONE 40mm (30mm) STANDARD OIL
3. SYMBOLISE TO SPEC 'D' (00-3816)
4. MATERIALS OF CONSTRUCTION:  
ROD - BLACK NITRIDED CARBON STEEL  
TUBE - BLACK EPOXY COATED CARBON STEEL  
VALVE - BRASS

**END FITS:**

ROD - STEEL, ZINC & TRIVALENT PASSIVATE  
TUBE - STEEL, ZINC & TRIVALENT PASSIVATE

Supplied by H. A. Guden Co., Inc. 800-344-6437 guden.com Guden P/N: 546334-1210



**CAMLOC MOTION CONTROL LTD**  
Manufacturers of *Camloc* Gas Springs  
15 New Star Road, Leicester, LE4 9JD, England  
Tel: +44 (0) 116 274 3600  
Email: info@camloc.com  
Website: www.camloc.com

**DRAWING DATA**

DRAWN: HL	PROJECT N°: SALES
DATE: 17/5/2023	
SCALE: 1:1	

TITLE:

**8-18 SWIFT & SURE  
GAS SPRING ASSEMBLY**

CUSTOMER: H A GUDEN

PART N°:  
**SWY8B3150209B3D**

REV: