

**NOTES:**

1. P1 STATIC FORCE AT 20°C: 2500N (+/-125N)
2. DAMPING ZONE 91mm (60mm) STANDARD OIL
3. SYMBOLISE TO SPEC 'D' (00-3816)
4. MATERIALS OF CONSTRUCTION:
 ROD - BLACK NITRIDED CARBON STEEL
 TUBE - BLACK EPOXY COATED CARBON STEEL
 VALVE - BRASS

END FITS:

ROD - STEEL, ZINC & TRIVALENT PASSIVATE
 TUBE - STEEL, ZINC & TRIVALENT PASSIVATE

Supplied by H. A. Guden Co., Inc. 800-344-6437 guden.com Guden P/N: 547616-1111

Camloc
 Motion Control

CAMLOC MOTION CONTROL LTD
 Manufacturers of *Camloc* Gas Springs
 15 New Star Road, Leicester, LE4 9JD, England
 Tel: +44 (0) 116 274 3600
 Email: info@camloc.com
 Website: www.camloc.com

DRAWING DATA

DRAWN: HL	PROJECT N°: SALES
DATE: 19/5/2023	
SCALE: 1:1	

TITLE:

**14-28 SWIFT & SURE
 GAS SPRING ASSEMBLY**

CUSTOMER: H A GUDEN

PART N°:
SWV4B6300375B6D

REV:

1



CAMLOC MOTION CONTROL LIMITED - THE DESIGN AND INFORMATION CONTAINED IN THIS DRAWING IS STRICTLY CONFIDENTIAL. IT IS THE EXCLUSIVE PROPERTY OF CAMLOC MOTION CONTROL LIMITED AND MUST NOT BE USED, COPIED OR REPRODUCED IN PART OR WHOLE WITHOUT WRITTEN PERMISSION FROM CAMLOC MOTION CONTROL LIMITED

**DRAWING IS
 COMPUTER GENERATED.
 DO NOT HAND MODIFY.**

**IF IN
 DOUBT,
 ASK.**

**DRAWING UNCONTROLLED WHEN
 PRINTED PLEASE CHECK ORDER
 REVISION LEVEL BEFORE MANUFACTURE**

DRAWING N°:
SWV4B6300375B6D_S