

H.A. GUDEN CO., INC.

REVIEWER:GL, IS
USER:AV, MC, ME, MI

FED. SUP CLASS
5340

SECTION A-A

70°-110°

82°-84°

HOLE AND PRESSING
OPTIONAL ON DASH
NO. 1

DASH NO.	A	B	C	D	E	F	G	H	J	L	M	P	WOOD SCREWS	
	±.06	±.06	±.06	±.06	±.01	DIA ±.03	±.03	±.03	±.03	±.03	±.01	MIN	QUANTITY	SIZE
1	3.62	3.62	2.94	3.75	.063	.34	1.91	2.00	2.75	1.71	.126	1.75	4 or 5	No. 10
2	4.50	4.88	4.19	5.19	.080	.44	2.81	2.50	3.75	2.53	.142	2.25	5	No. 12

NOTES:

- MATERIAL:** Mounting plate, cold rolled steel, temper No. 3 in accordance with QQ-S-698. Bail, steel annealed and cold finished in accordance with QQ-S-634.
- PROTECTIVE COATING:** Cadmium, Type II, Class 3 in accordance with QQ-P-416. Zinc, Type II, Class 3 in accordance with QQ-Z-325.
- DIMENSIONS:** All dimensions are in inches.
- PART NUMBER:** The MS number consists of the MS number plus the dash number. Example: MS35791-1.
- The MS part number includes the handle with screws, PF-S-111, Type I, Style 2S.
- For design feature purposes, this standard takes precedence over procurement documents referenced herein.
- Referenced documents shall be of the issue in effect on date of invitations for bid.
- The distance from the center of the mounting holes to the edge of the mounting plate shall be .375 minimum.
- The illustration is for identification and is not intended to restrict designs or shapes not dimensioned.
- Holes for wood screws shall be formed to accept flat head wood screws as indicated. Screw-heads of the size designated shall not extend above the top of the dimple.
- Effective 27 MAR 1970, dash numbers 21 and 10 are cancelled and superseded by dash number 1; dash numbers 22 and 11 are cancelled and superseded by dash number 2.
- The screw length shall be as furnished by the manufacturer or as suitable for the thickness of the chest material.

MATERIAL EXCEPTION SEE BELOW

P.A. WC Other Cust OS 82	TITLE HANDLE, BAIL-CHEST, SURFACE MOUNTING COUNTERSUNK HOLES	MILITARY STANDARD MS35791
PROCUREMENT SPECIFICATION NONE	SUPERSEDES: SKAX1	SHEET 1 OF 1

This military standard has been approved by the Department of Defense and is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

APPROVED 16 OCT 1956
REVISED (A) 21 NOV 1967 (B) 27 MAR 1970

DD FORM 1 SEP 57 672-1 (Coordinated)

PREVIOUS EDITIONS ARE OBSOLETE.

MOUNTING PLATE: JIS G3141 SPCC-SD
SIMILAR TO ASTM A1008
BAIL: JIS G3505 SWRM6K
SIMILAR TO AISI-SAE 1006